

LO-CW800-2FR4C

800G OSFP112 2xFR4 Transceiver, dual duplex LC, 2km

Features

The transceiver complies with common management interface specification (CMIS). The supported key features listed below allow host software to read and control the transceiver status through I2C.

- Adaptive Tx input equalization
- Programmable Rx output amplitude
- Programmable Rx output pre-cursor
- Programmable Rx output post-cursor
- Supply voltage monitoring (DDM_Voltage)
- Transceiver case temperature monitoring (DDM_Temperature)
- Tx transmit optical power monitoring for each lane (DDM_TxPower)
- Tx bias current monitoring for each lane (DDM_TxBias)
- Rx receive optical power monitoring for each lane (DDM_RxPower)
- Warning and alarm indication for each DDM function
- Tx & Rx LOL and LOS indication
- Tx fault indication
- Host and line side loopback capabilities
- Host and line side PRBS generator and checker capabilities
- CDB firmware upgrade capability
- Versatile diagnostics monitoring (VDM) capability (optional, additional power consumption increase)
- Other functions defined in CMIS

Applications

The transceiver is designed for Ethernet, Telecom and Infiniband use cases. The application advertisements listed below allow host software to select proper application following CMIS definition

- Application case 1, 2x400G FR4, 2 sets of 400G per port breakout connections
- Application case 2, 2x200G FR4, 2 sets of 200G per port breakout connections
- Application case 3, 8x100G FR, 8 of 100G per port breakout connections
- Application case 4, 1x800G FR8, 1 of 800G per port point to point connection
- Applications for backward compliance, refer to detailed application list below

Mixed applications of case 1 and case 3 are also supported.

Table 1 shows CMIS application advertisements list:

Table 1. CMIS Application advertisements

ApSel Code	Host Electrical Interface	Module Media Interface	Host and Media Lane Count	Host Lane Assignment
ApSel 1	50(400GAU1-4-L C2M)	1D(400GBASE-FR4)	44 (4:4)	11 (lanes 1,5)
ApSel 2	32(IB NDR)	1D(400GBASE-FR4)	44 (4:4)	11 (lanes 1,5)
ApSel 3	0F(200GAU1-4 C2M)	18(200GBASE-FR4)	44(4:4)	11 (lanes 1,5)
ApSel4	31(IB HDR)	18(200GBASE-FR4)	44 (4:4)	11 (lanes 1,5)
ApSel 5	4C(100GAU1-1-L C2M)	15(100GBASE-FR1)	11(1:1)	FF (lane 1,2,3,4,5,6,7,8)
ApSel 6	52(800G L C2M)	0(Undefined)	88(1:1)	01 (lanes 1)
ApSel 7	4F(400GAU1-4-S C2M)	1D (400GBASE-FR4)	44(4:4)	11 (lanes 1,5)
ApSel 8	4B(100GAU1-1-S C2M)	15(100GBASE-FR1)	11(1:1)	FF (lane 1,2,3,4,5,6,7,8)
ApSel 9	51(800G S C2M)	0 (Undefined)	88 (1:1)	01 (lanes 1)
ApSel 10	42(100CAU-4 FEC)	10(100G CWDM4 MSA)	44(4:4)	11 (lanes 1,5)
ApSel 11	30(IB EDR)	10(100G CWDM4 MSA)	44(4:4)	11 (lanes 1,5)

Description

This product is an 800Gb/s Octal Small Form-factor Pluggable (OSFP) optical module with top closed fin designed for 2km optical communication applications. The module converts 8 channels of 100Gb/s (PAM4)electrical input data to 2 sets of 4 CWDM optical signals and multiplexes them into 2 sets of a single channel for 425Gb/s optical transmission. Reversely, on the receiver side, the module optically de-multiplexes 2 sets of a single channel 425Gb/s signal inputs into 2 sets of 4 CWDM channel signals and converts them to 8 output channels of 106Gb/s electrical data.

The central wavelengths of the 4 CWDM channels are 1271, 1291, 1311 and 1331 nm as members of the CWDM wavelength grid defined in ITU-T G.694.2. It contains an optical Dual SMF LC duplex connector for the optical interface and a 60-pin connector for the electrical interface. To minimize the optical dispersion in the long-haul system, single-mode fiber (SMF) has to be applied in this module. Host FEC is required to support up to 2km fiber transmission.

I2C interface is supported to read and control the status of this product.

Figure 1 shows the transceiver block diagram




Figure 1. Transceiver Block Diagram

- OSFP form factor hot pluggable
- Top closed fin
- 2 sets of 4 CWDM lanes MUX/DEMUX design
- Electrical Interface: compliant to 800GAUI-8(8x106.25Gb/s) in IEEE 802.3ck
- Optical Interface: compliant to 400G-FR4 technical specification
- 16 Watts max
- CMIS compliance
- Case temperature range of 0°C to 70°C
- Dual SMF LC duplex connectors (5.25mm pitch)
- Up to 2km over SMF with KP4 FEC on host side

Pin Map and Description

The electrical interface of OSFP module consist of a 60 contacts edge connector as illustrated by the diagram in Figure 2, which defined in Clause 8.1 of OSFP MSA Specification.




Figure 2. MSA Compliant Connector

Table 2 shows the detailed pin list

Table 2 OSFP connector pin list

Pin#	Symbol	Description	Logic	Direction	Plug
1	GND		Ground		1
2	TX2p	Transmitter	CML-I	Input from Host	3
3	TX2n	Transmitter	CML-I	Input from Host	3
4	GND		Ground		1
5	TX4p	Transmitter	CML-I	Input from Host	3
6	TX4n	Transmitter	CML-I	Input from Host	3
7	GND		Ground		1
8	TX6p	Transmitter	CML-I	Input from Host	3
9	TX6n	Transmitter	CML-I	Input from Host	3
10	GND		Ground		1
11	TX8p	Transmitter	CML-I	Input from Host	3
12	TX8n	Transmitter	CML-I	Input from Host	3
13	GND		Ground		1
14	SCL	2-wire Serial	LVCMOS-I/O	Bi-directional	3
15	VCC	+3.3V Power		Power from	2
16	VCC	+3.3V Power		Power from	2
17	LPWn/PRSn	Low-Power	Multi-Level	Bi-directional	3

18	GND		Ground		1
19	RX7n	Receiver Data	CML-O	Output to Host	3
20	RX7p	Receiver Data	CML-O	Output to Host	3
21	GND		Ground		1
22	RX5n	Receiver Data	CML-O	Output to Host	3
23	RX5p	Receiver Data	CML-O	Output to Host	3
24	GND		Ground		1
25	RX3n	Receiver Data	CML-O	Output to Host	3
26	RX3p	Receiver Data	CML-O	Output to Host	3
27	GND		Ground		1
28	RX1n	Receiver Data	CML-O	Output to Host	3
29	RX1p	Receiver Data	CML-O	Output to Host	3
30	GND		Ground		1
31	GND		Ground		1
32	RX2p	Receiver Data	CML-O	Output to Host	3
33	RX2n	Receiver Data	CML-O	Output to Host	3
34	GND		Ground		1
35	RX4p	Receiver Data	CML-O	Output to Host	3
36	RX4n	Receiver Data	CML-O	Output to Host	3
37	GND		Ground		1
38	RX6p	Receiver Data	CML-O	Output to Host	3
39	RX6n	Receiver Data	CML-O	Output to Host	3
40	GND		Ground		1
41	RX8p	Receiver Data	CML-O	Output to Host	3
42	RX8n	Receiver Data	CML-O	Output to Host	3
43	GND		Ground		1
44	INT/RSTn	Module	Multi-Level	Bi-directional	3
45	VCC	+3.3V Power		Power from	2
46	VCC	+3.3V Power		Power from	2
47	SDA	2-wire Serial	LVCMOS-I/O	Bi-directional	3
48	GND		Ground		1
49	TX7n	Transmitter	CML-I	Input from Host	3
50	TX7p	Transmitter	CML-I	Input from Host	3
51	GND		Ground		1
52	TX5n	Transmitter	CML-I	Input from Host	3
53	TX5p	Transmitter	CML-I	Input from Host	3
54	GND		Ground		1
55	TX3n	Transmitter	CML-I	Input from Host	3
56	TX3p	Transmitter	CML-I	Input from Host	3
57	GND		Ground		1
58	TX1n	Transmitter	CML-I	Input from Host	3
59	TX1p	Transmitter	CML-I	Input from Host	3
60	GND		Ground		1

Table 3 shows the detailed control pins

Table 3. OSFPControl pins

Name	Direction	Description
SCL	BiDir	2-wire serial clock signal. Requires pull-up resistor to 3.3V on host
SDA	BiDir	2-wire serial data signal. Requires pull-up resistor to 3.3V on host.
LPWn/PRSn	Input/Output	Dual Function Signal . Low Power mode is an active-low input signal . Module Present is controlled by a pull-down resistor on the module which gets converted to an active-low output logic signal Voltage zones is shown as figure3.
INT/RSTn	Input/Output	Dual Function Signal . Reset is an active-low input signal . Interrupt is an active-high output signal Voltage zones is shown as figure 3.




Figure 3. Voltage Zones

Figure 4 shows the recommended power supply filter design




Figure 4. Recommended Power Supply Filter

Optical Port Description

The optical interface port is dual duplex LC. The transmit and receive optical lanes shall occupy the positions depicted in Figure 5 when looking into the MDI receptacle with the connector keyway feature on top.




Figure 5. Optical Media Dependent Interface port assignments

Absolute Maximum Ratings

It has to be noted that the operation in excess of any individual absolute maximum ratings might cause permanent damage to this module.

Parameter	Symbol	Min.	Max.	Unit	Notes
Storage Temperature	T _s	-40	85	degC	
Operating Case Temperature	T _{OP}	0	70	degC	
Power Supply Voltage	V _{CC}	-0.5	3.6	V	
Relative Humidity (non-condensation)	RH	0	85	%	

Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Operating Case Temperature	T _{OP}	0		70	degC	
Power Supply Voltage	V _{CC}	3.135	3.3	3.465	V	
Data Rate, each Lane			53.125		GBd	PAM4
Data Rate Accuracy		-100		100	ppm	

Pre-FEC Bit Error Ratio				2.4x10 ⁻⁴		
Post-FEC Bit Error Ratio				1x10 ⁻¹⁵		1
Link Distance	D	2		2000	m	2

Notes:

1.FEC provided by host system.

2.FEC required on host system to support maximum distance.

Electrical Characteristics

The following electrical characteristics are defined over the Recommended Operating Environment unless otherwise specified.

Parameter	Test Point	Min.	Typ.	Max.	Units	Notes
Power Consumption				16	W	
Supply current	ICC			4.84	A	
Module Input (each Lane)						
Signaling Rate, each Lane	TP1	53.125 ± 100 ppm			GBd	
DC Common-mode input Voltage	TP1	-0.35		2.85	V	
Single-ended input Voltage	TP1a	-0.4		3.3	V	
AC Common-mode RMS input Voltage Low-frequency,VCM LF Full-Band,VCM _{LF}	TP1a	32 80			mV	
Module stressed input test		IEEE 802.3ck 120G3.4.3				
Differential Peak-to-Peak input Voltage tolerance	TP1a	750			mV	
Common to Different Mode input Return Loss	TP1	IEEE802.3ck Equation 120G-2				

Effective input Return Loss	TP1	8.5			dB	
Differential input Termination Mismatch	TP1			10	%	
Module Output (each Lane)						
Signaling Rate, each lane	TP4	26.5625 ± 100 ppm			GBd	
Differential Peak-to-Peak	TP4				mV	
Output Voltage Short mode Long mode				600 845		
AC Common Mode Output Voltage, RMS Low-frequency,VCM _{LF} Full-Band,VCM _{LF}	TP4			32 80	mV	
Differential Termination Mismatch	TP4			10	%	
Eye height	TP4	15			mV	
Vertical eye closure, VEC	TP4			12	dB	
Common-mode to Differential mode output Return Loss	TP4	IEEE802.3ck Equation 120G-1			dB	
Effective output Return Loss	TP4	8.5			dB	
Output Transition time (20% to 80%)	TP4	8.5			ps	
DC Common-mode output Voltage	TP4	-350		2850	mV	
Differential termination mismatch	TP4			10	%	

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Wavelength Assignment	L0	1264.5	1271	1277.5	nm	
	L1	1284.5	1291	1297.5	nm	
	L2	1304.5	1311	1317.5	nm	
	L3	1324.5	1331	1337.5	nm	
	L4	1264.5	1271	1277.5	nm	
	L5	1284.5	1291	1297.5	nm	
	L6	1304.5	1311	1317.5	nm	
	L7	1324.5	1331	1337.5	nm	
Transmitter						
Data Rate, each Lane		53.125 ± 100 ppm			GBd	
Modulation Format		PAM4				
Side-mode Suppression Ratio	SMSR	30			dB	
Total average launch power				9.5	dBm	
Average Launch Power, each Lane	P _{AVG}	-3.2		3.5	dBm	1
Outer Optical Modulation Amplitude (OMA _{outer}), each Lane	P _{OMA}	Max(-0.2,-1.6+TDECQ)		3.7	dBm	2
Difference in launch power between any two lanes (OMA _{outer})				4	dB	
Transmitter and Dispersion Eye Closure for PAM4 (TDECQ), each Lane	TDECQ			3.4	dB	
Transmitter eye closure for PAM4 (TECQ), each Lane	TECQ			3.4	dB	
TDECQ-TECQ				2.5	dB	

Over/under-shoot				22	%	
Transmitter peak-to-peak power				4.5	dBm	
Extinction Ratio	ER	3.5			dB	
RIN _{17.1OMA}	RIN			-136	dB/Hz	
Optical Return Loss Tolerance	TOL			17.1	dB	
Transmitter Reflectance	R _T			-26	dB	
Transmitter Transition Time				17	ps	
Average Launch Power of OFF Transmitter, each Lane	P _{off}			-16	dBm	
Receiver						
Data Rate, each Lane		53.125 ± 100 ppm			GBd	
Modulation Format		PAM4				
Damage Threshold, each Lane	TH _d	4.5			dBm	3
Average Receive Power, each Lane		-7.2		3.5	dBm	4
Receive Power (OMA _{outer}), each Lane				3.7	dBm	
Difference in receive power between any two lanes (OMA _{outer})				4.1	dB	
Receiver Sensitivity (OMA _{outer}), each Lane	SEN					Equation (1)
Stressed Receiver Sensitivity (OMA _{outer}), each Lane	SRS					-2.6
Receiver Reflectance	R _R					-26
LOS Assert	LOSA	-15				-10.5
LOS De-assert	LOSD					-7.5
LOS Hysteresis	LOSH	0.5				

Conditions of Stress Receiver Sensitivity Test (Note 7)						
Stressed Eye Closure for PAM4 (SECQ), Lane under Test			3.4		dB	
OMA _{outer} of each aggressor lane			1.5		dBm	

Notes:

1. Average launch power, each lane (min) is informative and not the principal indicator of signal strength. A transmitter with launch power below this value cannot be compliant; however, a value above this does not ensure compliance.
2. The values for OMA_{outer}(min) vary with TDECQ. Figure 6 illustrates this along with the values for OMA_{outer}(max).
3. The receiver shall be able to tolerate, without damage, continuous exposure to a modulated optical input signal having this power level on one lane. The receiver does not have to operate correctly at this input power.
4. Average receive power, each lane (min) is informative and not the principal indicator of signal strength. A received power below this value cannot be compliant; however, a value above this does not ensure compliance.
5. Receiver sensitivity (OMA_{outer}) is informative and is defined for a transmitter with a value of TECQ up to 3.4 dB. Receiver sensitivity should meet Equation (1), which is illustrated in Figure 6.

$$RS = \max(-4.6, TECQ - 6.0) \text{ dBm} \quad (1)$$

Where:

RS is the receiver sensitivity, and
TECQ is the TECQ of the transmitter used to measure the receiver sensitivity.

6. Measured with conformance test signal at TP3 for the BER equal to 2.4×10^{-4} .
7. These test conditions are for measuring stressed receiver sensitivity. They are not characteristics of the receiver.




Figure 6. Illustration of Transmitter OMA_{outer} and Receiver Sensitivity Mask for 2x400G FR4

Digital Diagnostic Specifications

The following digital diagnostic characteristics are defined over the normal operating conditions unless otherwise specified.

Parameter	Symbol	Min.	Max.	Unit	Notes
Temperature monitor absolute error	DMI_Temp	-3	3	degC	Over operating temperature range
Supply voltage monitor absolute error	DMI_VCC	-0.1	0.1	V	Over full operating range
Channel RX power monitor absolute error	DMI_RX_Ch	-2	2	dB	1
Channel Bias current monitor	DMI_Ibias_Ch	-10%	10%	mA	
Channel TX power monitor absolute error	DMI_TX_Ch	-2	2	dB	1

Notes:

1. Due to measurement accuracy of different single mode fibers, there could be an additional +/-1 dB fluctuation, or a +/- 3 dB total accuracy.

Mechanical Drawing




Figure 7. Mechanical Outline

ESD

This transceiver is specified as ESD threshold 1kV for high speed data pins and 2kV for all other electrical input pins, tested per MIL-STD-883, Method 3015.4 /JESD22-A114-A (HBM). However, normal ESD precautions are still required during the handling of this module. This transceiver is shipped in ESD protective packaging. It should be removed from the packaging and handled only in an ESD protected environment.

Laser safety

This is a Class I Laser Product, or Class 1 Laser Product according to IEC/EN 60825-1:2014. This product complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019. Caution: Use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.

Ordering information

Part Number	Product Description
LO-CW800-2FR4C	800G, OSFP112, 2xFR4,dual duplexLC, 4 CWDM Lanes, up to 2km, 0°C~+70°C, Top-closed-fin, Pull tab