



REV.	DESCRIPTION OF CHANGE	REVIEWED BY	ISSUE DATE
A	FIRST ISSUE	LEO	2023-03-17










NOTES:
1.MATERIAL:
CAGE: COPPER ALLOY,NI PLATING,THICKNESS 0.25mm
MIDDLE CAGE: STAINLESS STEEL
HEAT SINK : ALUMINUM(SURFACE TREATMENT:BLACK OXIDE
HEAT SINK CLIP: STAINLESS STEEL
LIGHT PIPE: CLEAR POLYCARBONATE
2.PACKAGING: TRAY PACKAGING
3.TEMPERATURE RANGE:
OPERATING : −40°C TO +85°C
NON OPERATING : −55°C TO +105°C

RoHS 2011/65/EU


TITLE			LINK-PP INT'L TECHNOLOGY CO., LIMITED				
SFP+ 1X2 CAGE WITH EMI SPRING FINGER & WITH LIGHT PIPE & HEAT SINK							
PART NO. LP12BC01680D			GENNERAL TOLERANCE			UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	.X±0.25	.X±1°	SCALE:1:1	SHEET:1/4	REV:A
LEO	Kevin	Kevin	.XX±0.15	.XX±5°			
			.XXX±0.10				

RECOMMENDED PCB CONFIGURATION
WITH KEEP-OUT AREAS
SINGLE SIDED APPLICATIONS



CROSS-HATCHED AREA DENOTES
COMPONENT AND TRACE KEEP-OUT
(EXCEPT CHASSIS GROUND)

PCB LAYOUT
FOR SINGLE SIDE MOUNTING




DETAIL H
RECOMMENDED CONNECTOR LAYOUT
4X INDIVIDUALLY


RoHS 2011/65/EU

TITLE: SFP+ 1X2 CAGE WITH EMI SPRING FINGER & WITH LIGHT PIPE & HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED				
PART NO. LP12BC01680D			GENNERAL TOLERANCE			UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	.X±0.25	.X±1°	SCALE:1:1	SHEET:2/4	REV:A
LEO	Kevin	Kevin	.XX±0.15	.XX±5°			
			.XXX±0.10				

RECOMMENDED PCB CONFIGURATION
WITH KEEP-OUT AREAS
BELLY TO BELLY APPLICATIONS



CROSS-HATCHED AREA DENOTES
COMPONENT AND TRACE KEEP-OUT
(EXCEPT CHASSIS GROUND)





DETAIL H
RECOMMENDED CONNECTOR LAYOUT
4X INDIVIDUALLY

PCB LAYOUT
FOR BELLY TO BELLY SIDE MOUNTING

RoHS 2011/65/EU


TITLE: SFP+ 1X2 CAGE WITH EMI SPRING FINGER & WITH LIGHT PIPE & HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED				
PART NO.: LP12BC01680D			GENNERAL TOLERANCE			UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	.X±0.25	.X±1°	SCALE:1:1	SHEET:3/4	REV:A
LEO	Kevin	Kevin	.XX±0.15	.XX±5°			
			.XXX±0.10				






SECTION A–A

RECOMMENDED BEZEL DESIGN
SINGLE SIDED APPLICATIONS





SECTION A–A

RECOMMENDED BEZEL DESIGN
BELLY TO BELLY APPLICATIONS

RoHS
2011/65/EU

TITLE: SFP+ 1X2 CAGE WITH EMI SPRING FINGER & WITH LIGHT PIPE & HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED				
PART NO.: LP12BC01680D			GENNERAL TOLERANCE			UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	.X±0.25	.X±1°	SCALE:1:1	SHEET:4/4	REV:A
LEO	Kevin	Kevin	.XX±0.15	.XX±5°			
			.XXX±0.10				