




REV	DESCRIPTION OF CHANGE	REVIEWED BY	ISSUE DATE
A	FIRST ISSUE	LEO	2021-09-13











1. MATERIALS:
   CAGE UP: STAINLESS STEEL, 0.25 THICKNESS
   CAGE DOWN: STAINLESS STEEL, 0.25 THICKNESS
   PARTITION: STAINLESS STEEL
   EMI FINGERS: STAINLESS STEEL
   HEATSINK: ALUMINUM
   HEATSINK CLIP: STAINLESS STEEL
   LIGHT PIPE MATERIAL: CLEAR POLYCARBONATE
   CAP: THERMOPLASTIC 94V−0,BLACK

2. SURFACE FINISH:
   BODY CAGE: CLEANING
   EMI SPRING FINISH: CLEANING AND HOLE SEALING
   HEATSINK FINISH: BLACK ANODIZED
   HEATSINK CLIP FINISH: CLEANING

3. MATE WITH QSFP MSA COMPATIBLE TRANSCEIVER.


4. INSIDE SURFACE OF CASKET WHEN FULLY COMPRESSED.

5. REFERENCE DOCUMENTS:
   PRODUCT SPECIFICATION: SFF−8663

6. THIS PRODUCT COMPLY TO ROHS DIRECTIVE 2011/65/EU.

RoHS 2011/65/EU

TITLE: QSFP28 1X2 CAGE WITH EMI SPRING FINGER LIGHT PIPE HEAT SINK	LINK-PP INT'L TECHNOLOGY CO., LIMITED	
PART NO.: LP12FC01560D	GENNERAL TOLERANCE	UNIT:MM / SIZE:A4
APPROVE: LEO / CHECK: JAMES / DRAW: JAMES	◦ X±0.20, ◦ X±1°, ◦ XX±0.15, ◦ XX±5°, ◦ XXX±0.10	SCALE:1:1 / SHEET:1/5 / REV:A




NOTES:

1. THE NORMAL THICKNESS OF CUSTOMER SUPPLIED PC BOARD.(DIM. "F")
   SINGLE SIDED PC BOARD THICKNESS: 1.60mm MIN.
   BELLY TO BELLY PC BOARD THICKNESS: 3.0mm MIN.
2. GENERAL TOLERANCE: ±0.05.

RoHS 2011/65/EU


TITLE: QSFP28 1X2 CAGE WITH EMI SPRING FINGER LIGHT PIPE HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED			
PART NO.: LP12FC01560D			GENNERAL TOLERANCE		UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	◦ X±0.20	◦ X±1°	SCALE:1:1	SHEET:2/5 REV:A
LEO	JAMES	JAMES	◦ XX±0.15	◦ XX±5°		
			◦ XXX±0.10			


		THE DIMENSION FOR MATING BEZEL (UNIT: mm)						
CODE	L/P APPEARANCE	L/P CUT-OUT	L/P PITCH (FRONT)	L/P PITCH (REAR)	L/P HEIGHT	BEZEL THICKNESS	LED HEIGHT	REMARK
0	NO L/P							WITHOUT LIGHT PIPE
A	ROUND	ø2.67	4.00(Equal)	1,4=15.75 2,3=3.40	7.86	1.60	0.8~1.1	APPLIES TO QUAD L/P
		①	②	③	④	⑤	⑥	




RoHS 2011/65/EU

TITLE: QSFP28 1X2 CAGE WITH EMI SPRING FINGER LIGHT PIPE HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED			
PART NO.: LP12FC01560D			GENNERAL TOLERANCE		UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	◦ X±0.20	◦ X±1°	SCALE:1:1	SHEET:3/5 REV:A
LEO	JAMES	JAMES	◦ XX±0.15	◦ XX±5°		
			◦ XXX±0.10			








NOTES:


1. DATUM X & Y ARE ESTABLISHED BY THE CUSTOMER'S FIDUCIAL
2. DATUM A IS THE TOP SURFACE OF THE HOST BOARD
3. LOCATION OF THE EDGE OF PCB IS APPLICATION SPECIFIC
4. BASELINE FOR THESE DIMENSIONS IS THE CENTER OF COMPLIANT PIN HOLE.
5. FINISHED HOLE SIZE
6. UNPLATED THRU HOLE.
7. REFER TO SFF8662 FOR CONNECTOR FOOTING DIMENSIONS

RoHS 2011/65/EU

TITLE: QSFP28 1X2 CAGE WITH EMI SPRING FINGER LIGHT PIPE HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED			
PART NO.: LP12FC01560D			GENNERAL TOLERANCE		UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	◦ X±0.20	◦ X±1°	SCALE:1:1	SHEET:4/5 REV:A
LEO	JAMES	JAMES	◦ XX±0.15	◦ XX±5°		
			◦ XXX±0.10			



RECOMMENDED BELLY TO BELLY PC BOARD LAYOUT



FINISHED HOLE SIZE SPECS

RoHS 2011/65/EU

TITLE: QSFP28 1X2 CAGE WITH EMI SPRING FINGER LIGHT PIPE HEAT SINK			LINK-PP INT'L TECHNOLOGY CO., LIMITED			
PART NO.: LP12FC01560D			GENNERAL TOLERANCE		UNIT:MM	SIZE:A4
APPROVE	CHECK	DRAW	◦ X±0.20	◦ X±1°	SCALE:1:1	SHEET:5/5 REV:A
LEO	JAMES	JAMES	◦ XX±0.15	◦ XX±5°		
			◦ XXX±0.10			