

LS-MM8532E-S3C

SFP28 8G/16G/32G 850nm 300m DDMI

Product Features

- Up to 28.05Gbps Data Links
- Support 8.5Gb/s and 14.25Gb/s
- 850nm VCSEL laser transmitter and PIN receiver
- Multimode Fiber (MMF) and 300m on OM4 MMF
- Compliant with SFP+ MSA and SFF-8472 with duplex LC receptacle
- Hot-pluggable SFP28 footprint
- Duplex LC receptacles
- Low power dissipation
- RoHS compliant and lead-free
- Support Digital Diagnostic Monitor interface
- Single +3.3V power supply
- 0°C to +70°C case operating temperature

Applications

- 28.05 Gb/s Fibre Channel


Compliance

- SFF-8472
- SFF-8402
- SFF-8432
- SFF-8431

Description

The SFP28 transceivers are high performance, cost effective modules supporting data rate of 8.5Gbps, 14.25Gbps, 28.05Gbps over multimode fiber.

The transceiver consists of three sections: a VCSEL laser transmitter, a PIN photodiode integrated with a trans-impedance preamplifier (TIA) and MCU control unit. All modules satisfy class I laser safety requirements. The transceivers are compatible with SFP Multi-Source Agreement and SFF-8472 digital diagnostics functions.



Transceiver functional diagram

Absolute Maximum Ratings

Parameter	Symbol	Min	Type	Max	Unit	Ref.
Maximum Supply Voltage	Vcc	-0.5		3.6	V	
Storage Temperature	TS	-40		85	°C	1
Case Operating Temperature	TOP	0		70	°C	
Relative Humidity	RH	0		85	%	2

Notes:

- 1.Limited by the fiber cable jacket, not the active ends.
- 2.Non-condensing.

Optical Characteristics (TOP = 0°C to 70°C, VCC = 3.3 ± 5% Volts)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
Transmitter						
Center Wavelength	λ_c	840	850	860	nm	
RMS Spectral Width	Pm			0.6	nm	
Average Output Power	Pavg	-8.4		2.4	dBm	
Optical Modulation Amplitude (OMA)	Poma	-6.4		3	dBm	
Extinction Ratio	ER	2			dB	
Transmitter Dispersion Penalty	TDEC			4.3	dB	
Optical Return Loss Tolerance	TOL			12	dB	
Transmitter OFF Output Power	POff			-30	dBm	
Transmitter eye mask definition {X1, X2, X3, Y1, Y2, Y3}, Hit ratio 1.5E-3		{0.3, 0.38, 0.45, 0.35, 0.41, 0.5}				
Receiver						
Center Wavelength	λ_c	840	850	860	nm	
Receiver Stress Sensitivity, OMA				-5.2	dBm	
Receiver Sensitivity, Average Power				-10.3	dBm	
Receiver Reflectance	Rfl			-26	dBm	
Loss of Signal Assert	P _A	-30			dBm	
Loss of Signal De-assert	P _D			-13	dBm	
LOS Hysteresis	P _D - P _A	0.5			dB	

Electrical Characteristics (TOP = 0°C to 70°C, VCC = 3.3 ± 5% Volts)


Parameter	Symbol	Min	Type	Max	Unit	Ref.
Supply Voltage	Vcc	3.135	3.3	3.465	V	
Supply Current	Icc			300	mA	
Transmitter						

Input differential impedance	Rin		100			1
Differential data input swing	Vin, pp	200		1000	mV	
Transmit Disable Voltage	VD	2		VCC	V	
Transmit Enable Voltage	VEN	Vee		Vee+0.8	V	
Receiver						
Differential data output swing	Vout, pp	200		1000	mV	2
LOS Fault	VLOS_fault	2		Vcc	V	3
LOS Normal	VLOS_norm	Vee		Vee+0.8	V	3
Power Supply Noise Tolerance	VCCT/VCCR	Per SFF-8431 Rev 4.1			mVpp	

Notes:

1. Connected directly to TX data input pins.AC coupling from pins into laser driver IC.
2. Into 100Ω differential termination.
3. Measured with Module Compliance Test Board and OMA test pattern. Use of four 1's and four 0's in sequence in the PRBS^9 is an acceptable alternative. SFF-8431 Rev 4.1


Digital Diagnostic Memory Map



Digital Diagnostic Monitoring Information

Parameter	Unit	Accuracy
Case Temperature	°C	±3
Supply Voltage	V	±3%
Tx Bias Current	mA	±10%
Tx Optical Power	dB	±3
Rx Optical Power	dB	±3

Pin Diagram



Pinout of Connector Block on Host Board

Pin Descriptions


Pin	Symbol	Name/Description	NOTE
1	VEET	Module transmitter ground	1
2	Fault	Module transmitter Fault	2

3	Disable	Transmitter Disable; Turns off transmitter laser output	3
4	SDL	2 wire serial interface data input/output (SDA)	4
5	SCL	2 wire serial interface clock input (SCL)	4
6	MOD-ABS	Module Absent, connect to VeeR or VeeT in the module	2
7	RS0	Rate select0: module inputs and are pulled low to VeeT with >30 kΩ resistors in the module.	
8	LOS	Receiver Loss of Signal Indication	
9	RS1	Rate select1: module inputs and are pulled low to VeeT with >30 kΩ resistors in the module.	
10	VeeR	Module receiver ground	1
11	VeeR	Module receiver ground	1
12	RD-	Receiver inverted data out put	
13	RD+	Receiver non-inverted data out put	
14	VeeR	Module receiver ground	1
15	VccR	Module receiver 3.3V supply	
16	VccT	Module transmitter 3.3V supply	
17	VeeT	Module transmitter ground	1
18	TD+	Transmitter non-inverted data out put	
19	TD-	Transmitter inverted data out put	
20	VeeT	Module transmitter ground	1


Notes:

1. The module ground pins shall be isolated from the module case.
2. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.
3. This pin shall be pulled up with 4.7K-10Kohms to VccT in the module.
4. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.

Recommended Interface Circuit



Mechanical Dimensions



Unit: mm

	L	L1	L2	L3	W	W1	W2	H	H1	H2
MAX	56.9	31.2	41.95	47.7	13.8	10.2	14.0	8.6	0.6	11.5
Typical	56.7	31.0	41.80	47.5	13.7	10.0	-	8.5	0.5	11.3
MIN	56.5	30.8	41.65	47.3	13.5	9.8	-	8.4	0.4	11.1

Ordering Information

Part No.	Bit Rate (Gbps)	Laser (nm)	Distance	Fiber Type	DDMI	Connector	Temp
LS-MM8532E-S3C	8.5, 14.25, 28.05	850	300m OM4	MMF	YES	LC	0°C ~+70°C